



INDUSTRY POLYPROPYLENE (PP) STRAPPING

PRODUCT INFORMATION

Polypropylene strapping is a good choice when it comes to the inexpensive and user-friendly bundling and strapping of your laden pallets and despatch units, especially for lighter weight strapping (up to around 450 kg). Van der Windt offers a range of PP strapping in various standard colours, for manual or machine use, in various widths, strengths and roll lengths. Simple and economical; Van der Windt offers you the solutions for all your transportation requirements!



SUPPLY INFORMATION

The table below provides an overview of the many options and applications for PP strapping.

We also offer a wide choice of accessories such as dispensers, tensioning apparatus, seals and clamps.

WIDE PP STRAPPING

WIDTH X THICKNESS (MM)	CORE (MM)	LENGTH PER REEL (M)	AVERAGE STRENGTH (KG-F)	
8	x 0,55	200	4000	102
	x 0,55	280	3600	102
	x 0,63	200	4000	102
9	x 0,55	200	4000	102
	x 0,55	280	3500	102
	x 0,63	200	3600	115
	x 0,63	280	3000	115
	x SA*	200	3000	102
12	x 0,55	200	3000	130
	x 0,55	280	2500	130
	x 0,63	200	3000	150
	x 0,63	280	2100	150
	x 0,63	406	2500	195
	x 0,75	200	2300	200
	x 0,75	280	2000	200
	x 0,75	406	2200	200
	x 0,83	406	1800	240
	x 0,95	406	1800	305
15,5	x 0,55	200	2500	190
	x 0,55	280	1900	190
	x 0,63	200	2200	220
	x 0,63	280	1600	220
	x 0,75	406	1800	240
	x 0,85	406	1300	340

* Special product for semi-automatic use

www.vanderwindt.com

Nieuweweg 10, P.O. Box 22, 2675 ZG Honselersdijk, The Netherlands, Tel. +31(0) 174 636111, Fax +31(0) 174 620554, info@vanderwindt.com